

TECHNICAL SPECIFICATIONS

	H50-500	H150-1000	H150-1500	H150-2100	H150-3000
Temperature range (°C)	-5 ~ +35	+8 ~ +35	+8 ~ +35	+8 ~ +35	+8 ~ +35
Temperature stability (°C)	±0.3	±0.1	±0.1	±0.1	±0.1
Temperature control mode	P.I.D.				
Cooling capacity (W)	500	1000	1500	2100	3000
Pump flux (L/min)	3 @10psi	5 @60psi	5 @60psi	13 @60psi	13 @60psi
Pump power (W)	25	120	120	250	250
Pump type	Magnetic				
Heat exchanger model	Board				
Dimension (LxWxH cm)	48x25x50	56x36x59	65x39x63	74x46x71	74x46x71
Weight (Kg)	28	52	68	83	83
Power supply voltage	230V 50/60Hz				
Ordering information	LW500	LW1000N	LW1500N	LW2100N	LW3000N

	H150-5000	H150-7000	H150-9000	H150-1000LT	H150-2100LT
Temperature range (°C)	+8 ~ +35	+8 ~ +35	+8 ~ +35	-20 ~ +35	-20 ~ +35
Temperature stability (°C)	±0.2	±0.2	±0.2	±0.1	±0.1
Temperature control mode	P.I.D.				
Cooling capacity (W)	5000	7000	9000	1000	2100
Pump flux (L/min)	13 @60psi	13 @60psi	13 @60psi	5 @60psi	13 @60psi
Pump power (W)	250	250	250	120	250
Pump type	Magnetic				
Heat exchanger model	Board				
Dimension (LxWxH cm)	69x64x110	69x64x110	69x64x110	56x36x59	74x46x71
Weight (Kg)	162	164	164	52	83
Power supply voltage	230V 50Hz	400V 50Hz 440V 60Hz	400V 50Hz 440V 60Hz	230V 50/60Hz	230V 50/60Hz
Ordering information	LW5000N	LW7000N	LW9000N	LW1000NLT	LW2100NLT

Customized versions available